



ITEM	QTY -45	P/N	DESCRIPTION
1	X	B67-43001-45	LONGITUDINAL SUPPORT
3	1	B67-43001-97	CLEVIS
4	1	B67-43001-357	TUBE ARM
5	1	D3447-1	ROUND SPACER
6	1	D3447-5	CLEVIS
8	1	30345T21	LANYARD
9	1	AN4-13A	BOLT
10	1	CR3213-4-2	RIVET (OR BSP43-2)
11	1	MS17984-C410	QUICK RELEASE PIN
12	1	MS21042L4	NUT
13	1	MS171534	SPRING SLOTTED TENSION PIN (OR 240107)
14	2	NAS1149D0416J	WASHER
15	1	NAS1149DN416J	WASHER

RELEASED
2009-08-24

C	REDRAWN PREMIER AVIATION DRAWING IAW DART QSI 018 AND QSI 043. FOR PREVIOUS REVISIONS, REFER TO SHEET 13 OF PREMIER AVIATION DRAWING No. B67-43001. REASON: SEE PAR#09-011.	MB	09.06.25
REV.	DESCRIPTION	BY	DATE
DESIGN	RW	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
DRAWN			
CHECKED	ASS	DRAWING NO.	REV. C
MFG. APPR.		B67-43001-45	SHEET 1 OF 2
APPROVED		TITLE	SCALE
DE APPR.	N/A	LONGITUDINAL SUPPORT	NTS
DATE	09.06.25	COPYRIGHT © 1995 BY DART AEROSPACE LTD THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.	

B67-43001-97
2 CLEVIS

B67-43001-357
2 TUBE ARM

10 CR3213-4-2 RIVET
NAS1149DN416J WASHER
(30345T21 LANYARD NOT SHOWN
ON THIS VIEW FOR CLARITY)

D3447-1
ROUND SPACER

AN4-13A BOLT
NAS1149D0416J WASHER, 2X
MS21042L4 NUT

10 30345T21 LANYARD

MS17984-C410
QUICK RELEASE
PIN

0.50
8

MS171534 2 8
SPRING SLOTTED TENSION PIN

9
2 PL

D3447-5
CLEVIS

B67-43001-45 LONGITUDINAL SUPPORT

RELEASED
2009-09-24

NOTES:

- 1) MATERIAL: N/A
- 2) FINISH: POWDER COAT GREEN SANDTEX (4.3.5.8) PER DART QSI 005 4.3
- 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
- 4) UNITS: INCHES UNLESS OTHERWISE NOTED
- 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
- 6) IDENTIFICATION: N/A
- 7) WEIGHT: 0.99 lbs
- 8) PRIOR TO POWDER COAT, ALIGN B67-43001-97 ON B67-43001-357 AS SHOWN AND DRILL A $\varnothing 0.129$ HOLE THROUGH BOTH PARTS.
FASTEN B67-43001-97 TO B67-43001-357 USING MS171534 SPRING SLOTTED PIN.
- 9) MASK PRIOR TO POWDER COAT
- 10) BEFORE OR AFTER POWDER COAT, DRILL A $\varnothing 0.129$ HOLE IN B67-43001-357 TO INSTALL THE LANYARD. DRILL THROUGH ONE WALL ONLY.
AFTER POWDER COAT, INSTALL 30345T21 LANYARD ON B67-43001-357 AS SHOWN USING CR3213-4 TYPE RIVET AND NAS1149DN416J WASHER.

DESIGN	RW	DART AEROSPACE LTD	
DRAWN		HAWKESBURY, ONTARIO, CANADA	
CHECKED	SS	DRAWING NO.	REV. C
MFG. APPR.	AD	B67-43001-45	SHEET 2 OF 2
APPROVED	N/A	TITLE	SCALE
DE APPR.		LONGITUDINAL SUPPORT	NTS
DATE	09.06.25	COPYRIGHT © 1995 BY DART AEROSPACE LTD THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.	